



Labelmate Product Overview

Un- and Rewinders



Product	Rewinders	Unwinders	Label dispensers	Label counters
Description	Page 369	Page 369	Page 369	Page 369
Type	Heavy duty and low cost rewinders	Heavy duty unwinders	Automatic label dispensers	Heavy duty label counters
Core diameter	UNI-CAT-1-INCH: 25.4 mm; UNI-CAT, MC-11, MC-11+, TWIN-CAT: 25 mm to 101 mm; UNI-CAT-STANDARD, UNI-CAT-CHUCK, UNI-CAT-10-INCHES, MC-10, MC-10+: 38 mm to 100 mm	UCAT-1: 25 mm to 101 mm; UCAT-3: 25 mm to 101 mm; UCAT-40: 76 mm; UCAT-S: 38 mm to 100 mm	LD-100: 38 mm to 78 mm; LD-200: 38 mm to 76 mm; LD-300: 38 mm to 76 mm	RRC-330: 25 mm to 101 mm; Distri-COUNT: 25.4 mm to 76 mm
Roll diameter	UNI-CAT-STANDARD/-CHUCK/-10-INCHES: 300 mm UNI-CAT-ACH/-1-INCH: 220 mm to 280 mm; MC-10, MC-10+, MC-11, MC-11+, TWIN-CAT: 220 mm	UCAT-1: up to 300 mm; UCAT-3: up to 300 mm; UCAT-40: up to 400 mm; UCAT-S: up to 300 mm	LD-100: up to 220 mm; LD-200: up to 220 mm; LD-300: up to 300 mm	RRC-330: 330 mm; Distri-COUNT: 220 mm
Media width	UNI-CAT: up to 255 mm MC-10, MC-10+: up to 125 mm; MC-11, MC-11+: up to 115 mm; TWIN-CAT: up to 270 mm; S-100: 170 mm; S-200: 255 mm	UCAT-1: up to 255 mm; UCAT-3: up to 255 mm; UCAT-40: up to 170 mm; UCAT-S: up to 155 mm	LD-100: up to 115 mm; LD-200: up to 165 mm; LD-300: up to 218 mm	RRC-330: 152 mm; Distri-COUNT: max. 115 mm
Speed	UNI-CAT: up to 125cm/sec., TWIN-CAT: up to 125 cm/sec., MC-10, MC-10+, MC-11, MC-11+: up to 50 cm/sec., S-100/S-200: 125 cm/sec., limited by printer	UCAT-3, UCAT-40: up to 125 cm/sec.; UCAT-1, UCAT-S: same as printer	LD-100: 11 cm/sec.; LD-200: 11 cm/sec.; LD-300: 11 cm/sec.	RRC-330: 72 to 235 cm/sec.; Distri-COUNT: n/a
Features/ options	Optional: tension arm, quick chucks, version with geared motor, foot switch, adjustable reel tension, potentiometer, label slitter, zero tension loop	Optional: tension arm, quick chucks	Optional: counter (pre-settable), core expansion, battery, supports transparent and dark labels (LD-100-U, LD-200-U)	Optional: encoder for length measurement + Battery pack, Sensor for transparent and black labels
Weight	5.3 kg to 18.6 kg	6 kg to 13 kg	6 kg to 8 kg	16 kg to 20 kg
Dimensions (W x D x H)	UNI-CAT-STANDARD: 300 x 350 x 320 mm UNI-CAT-CHUCK: 300 x 385 x 320 mm UNI-CAT-ACH: 280 x 310 x 310 mm UNI-CAT-10-INCHES: 300 x 455 x 320 mm UNI-CAT-1-INCH: 220 x 350 x 280 mm; MC-10, MC-10+, MC-11, MC-11+: 305 x 220 x 195 mm; TWIN-CAT: 370 x 180 x 470 mm; S-100: 280 x 355 x 250 mm; S-200: 280 x 435 x 250 mm	UCAT-1: 350 x 300 x 320 mm; UCAT-3: 350 x 300 x 320 mm; UCAT-40: 450 x 400 x 460 mm; UCAT-S: 365 x 300 x 320 mm	LD-100: 200 x 210 x 270 mm; LD-200: 200 x 270 x 270 mm; LD-300: 250 x 300 x 295 mm	RRC-330: 330 x 830 x 330 mm; Distri-COUNT: 232 x 295 x 222 mm
Warranty	5 years (SR-100/SR-200: 3 years)		3 years	